

PREMIUM INTERIOR LOW SHEEN ACRYLIC

LINE 4375
SEPTEMBER 2013
PAGE 1 OF 3



Description & Uses

Solver Ultra Interior Low Sheen Acrylic is a washable, hardwearing water-based acrylic paint which delivers a premium quality finish on residential and commercial interior walls. Specifically formulated for the trade painter this premium product has superior application properties, with high opacity to achieve a uniform, professional finish.

Features & Benefits

- | | |
|---|---|
| <ul style="list-style-type: none"> • Uniform finish • High washability, resists stains • Smooth, even finish | <ul style="list-style-type: none"> • Superior opacity • Wide colour selection • Easy, fast application |
|---|---|

Colours

Colours available tinted from white, light, mid and strong tint bases.

Low Sheen (Gloss level 5 - 10 at 60 degrees)

Environmental Data & Certifications



Approved to Australia Paint Approval Scheme Specification APAS 0260/3.
Australian Standard AS3730.3

PREMIUM INTERIOR LOW SHEEN ACRYLIC

LINE 4375
SEPTEMBER 2013
PAGE 2 OF 3

Properties & Performance Guide

Dry & Recoat Times	<p>Surface Dry - 30 minutes Recoat - 2 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.</p>
Coverage per Coat	Up to 16 M ² /L depending on the surface texture, porosity and method of application.
Film Thickness	<p>Wet Film Thickness (WFT) - 63 microns minimum Dry Film Thickness (DFT) - 26 microns minimum</p>
Thinning	Thinning is generally not required. If necessary to aid spray atomisation, thin with up to 5% water.
Clean Up	<p>Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.</p>
VOC (Volatile Organic Compounds)	VOC < 50g/Litre.

Recommended Substrate Conditions & Preparation

<p>Surfaces are to be suitably prepared in accordance with proper trade practices. Ensure the surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed. Sand enamel painted surfaces to remove gloss. Fill holes and cracks with a suitable filler and sand lightly to an even finish. Test soundness of previously painted surfaces before painting. Unsound surfaces should be stripped before repainting.</p>	
Previously painted surfaces, new paper-faced plasterboard, unpainted brick, cement render, fibre cement or masonry	Apply one coat of Solver Ultra Acrylic Sealer Undercoat (Line 4325).
Interior bare timber and MDF	Apply one coat of Solver Ultra Acrylic Sealer Undercoat (Line 4325). On tannin rich timber first apply one coat of Solver Ultra Primer Sealer Undercoat (Line 4320).
New set plaster	Apply one coat of Solver Wall-Sealer (Line 4129) or Solver Preps Acrylic Plaster Sealer (Line 4360).
Stain Sealing	Seal with Solver Quick Drying Multi Block Stain Sealer (Line 4747) (solvent based).
Mould & Fungus Infected Areas	<p>Clean surface with household bleach then rinse well with clean water. Treat the surface with Solver Sterilizing Wall-Wash (Line 4651). If abnormal conditions are expected e.g. condensation, dampness etc, Solver Anti-Fungus Additive No. 1 (Line 4651) may be added to the paint for extra protection. For normal conditions this addition will not be necessary.</p>

PREMIUM INTERIOR LOW SHEEN ACRYLIC

LINE 4375
SEPTEMBER 2013
PAGE 3 OF 3

Application Guide

Stir well before and during use with a broad paddle reaching to the bottom of the can.

Apply two full, even coats by brush, roller or airless spray.
Use a medium nap (12mm pile) synthetic roller on smooth and semi-smooth surfaces.
Use a longer nap (20mm pile) synthetic roller on rough surfaces, e.g. Besser Block.
Use a 13 or 15 thou Tip for airless spray.
Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.

Additional Data

Available in 4 & 10 litres, white also available in 15 litre containers.
If the paint has been tinted, check that the colour is suitable for your requirements before application. For best results and colour consistency, tinted paint should be boxed and thoroughly mixed on site.
Avoid exposure to steam and condensation for 48 hours after application of final coat.
Containers must be secured and stored upright during transit.
Containers must not be exposed to excessive heat or cold.
The use of proprietary additives other than those manufactured by Solver is not recommended.
Do not use for any other purpose other than as specified in our literature.

Safety Data

First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Aust) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. Avoid prolonged breathing of vapour. Wash hands thoroughly after use.
Further Information	For further information to refer to the Safety Data Sheet available on the Solver website. www.solvepaints.com.au or contact the Solver Hotline on 132 101.

- This information is provided with respect to the listed Solver products. Valspar (WPC) recommends that:
(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Valspar; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.
- Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
- To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Solver® & Solver Ultra®, are registered trademarks of Valspar (WPC) Pty Ltd ABN 65 007 527 371.

INFORMATION HOTLINE: Ph: 132 101 (AUSTRALIA)